

CULTIFLEX



Combined Cultiflex CTFI T

Cultiflex CTFI T

Half-brought version
Working width from 4.00 m to 6.00 m
Transport width 2.50 m

Innovative machine for the precision preparation of the seed bed. Very versatile machine, composed with different working elements for best adapting to the different types of soil and to the exigencies of the customers. Available on brought and half - brought version. Hydraulically foldable for reducing the transport on road.



Rear double roller

Particular of working elements



ma/ag
MACCHINE AGRICOLE S.r.l.

HALF – BROUGHT VERSION EQUIPMENT

- Arm lifting device
- Couple of row breakers (at demand)
- Front levelling bar
- Front levelling breaking cage roller diameter 500 mm with tubes
- Flex springs 32x12 “flat” or “S” type kit, arranged on 4 working ranges, mechanically depth regulation (hydraulically at demand)
- Rear breaking cage roller diameter 500 mm with plates
- Cage finishing roller diameter 320 mm with plates, with dolly device springs
- Hydraulic chariot for the transport on road
- Light bar



ACCESSORIES AT DEMAND

- Hydraulic handling of the springs group
- Square spring kit 25x25 mm with triangular dovetail shares
- Couple of row breakers
- Rear levelling bar
- Oversize wheels 400/60-15.5
- Rear kit for hooking up seed drill

MODELS AVAILABLE

| Model | Working Width (m) | Transport Width (m) | Weight (Kg) | HP |
|--------------|-------------------|---------------------|-------------|-----------|
| CTFI 40T / 2 | 4,00 | 2,55 | 2640 | 150 / 170 |
| CTFI 50T / 2 | 5,00 | 2,55 | 3210 | 170 / 190 |
| CTFI 60T / 2 | 6,00 | 2,55 | 3850 | 190 / 240 |

COMBINED CULTIFLEX

- Transport width 2.50 m
- High speed 7/12 km/h with a higher reduction in production costs (manpower, fuel, wear tractor)
- Low HP needed and very large working soil
- Less land compaction
- Working depth up to 20 cm
- Better water retention of the soil
- Decrease of the erosion
- Possibility to apply a seeding kit

ma/ag
S.r.l.
MACCHINE AGRICOLE



26011 Casalbuttano (CR) ITALIA
Via Giovanni Paolo II, 12
Tel. +39 0374 362 680 Fax +39 0374 362 280
www.ma-ag.com info@ma-ag.com

